

Homework problems:

1. You are being offered the following programming assignment:

Intel Septium code optimisation

A large company producing embedded systems software would like to have a code optimiser that, given as input any machine language program for the new Intel Septium processor, will output the smallest machine language program that is functionally equivalent to the given one (i.e. has the same input-output behaviour).

Your comments? Under what conditions would you accept the assignment? Justify your answer.

2. Consider application programs running under some given operating system. Let us say that a program P is *dangerous*, if it on some input modifies the operating system's system files. A *general purpose virus tester* is a program that receives as input an arbitrary application program text P , analyses it and returns output "DANGER", if the program is dangerous, and "OK" otherwise. Show that if any dangerous programs exist at all, then general-purpose virus testing is impossible.
3. Design unrestricted grammars (general rewriting systems) that generate the following languages:
 - (a) $\{w \in \{a, b, c\}^* \mid w \text{ contains equally many } a\text{'s, } b\text{'s and } c\text{'s}\}$,
 - (b) $\{a^{2^n} \mid n \geq 0\}$.

Demonstration problems:

4. Prove, without appealing to Rice's theorem, that the following problem is undecidable:

Given a Turing machine M ; does M accept the empty string?

5. Prove the following connections between recursive functions and languages:
 - (i) A language $A \subseteq \Sigma^*$ is recursive ("Turing-decidable"), if and only if its characteristic function

$$\chi_A : \Sigma^* \rightarrow \{0, 1\}, \quad \chi_A(x) = \begin{cases} 1, & \text{if } x \in A; \\ 0, & \text{if } x \notin A \end{cases}$$

is a recursive ("Turing-computable") function.

- (ii) A language $A \subseteq \Sigma^*$ is recursively enumerable ("semidecidable", "Turing-recognisable"), if and only if either $A = \emptyset$ or there exists a recursive function $g : \{0, 1\}^* \rightarrow \Sigma^*$ such that

$$A = \{g(x) \mid x \in \{0, 1\}^*\}.$$